

# Material Safety Data Sheet

according to Regulation (EC) 1907/2006, Article 31

Product name: **TPC 128**

Revision : 25.05.2018

Page : 1 / 8

 Teca-Print

Version Number: 6

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

### 1.1 Product identifier

Trade name: **TPC 128**

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Printing inks

### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

TECA-PRINT AG

Bohlstrasse 17

Postfach

CH-8240 Thayngen

Tel.: 0041 / 52 645 20 00

e-mail: info@teca-print.com

Further information obtainable from: Product safety department

1.4 Emergency telephone number: Tox Center Zürich: 0041 - 44 251 51 51

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3

H226

Flammable liquid and



GHS09 environment

Aquatic Chronic 2 H411

Toxic to aquatic life with long lasting effects.



GHS07

STOT SE 3

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

### 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02 GHS07 GHS09

Signal word Warning

Hazard-determining components of labelling:

Solvent naphtha (petroleum), light arom.

Hazard statements

H226 Flammable liquid and vapour.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

GB

# Material Safety Data Sheet

according to Regulation (EC) 1907/2006, Article 31

Product name: TPC 128

Revision : 25.05.2018

Page : 2 / 8



Version Number: 6

(Contd. of page 1)

## · Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.
- P24 Use explosion-proof electrical/ventilating/lighting equipment.
- 1 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P26 Wear protective gloves / eye protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

## · Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.  
Contains isobutyl methacrylate. May produce an allergic reaction.

## · 2.3 Other hazards

## · Results of PBT and vPvB assessment

- PBT: Not applicable.  
· vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

### · 3.2 Chemical characterisation: Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

#### · Dangerous components:

CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336	10-25%
EC number: 918-811-1	Hydrocarbon, C10, aromatics, <1% naphthalene ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336	10-25%
CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	2.5-10%
CAS: 1333-86-4 EINECS: 215-609-9	Carbon black substance with a Community workplace exposure limit	2.5-10%
CAS: 1330-20-7	Xylene, mixed isomers ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; ⚠ Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; ⚠ Acute Tox. 4, H332; ⚠ Eye Irrit. 2, H319	1-2.5%
CAS: 97-86-9 EINECS: 202-613-0	isobutyl methacrylate ⚠ Flam. Liq. 3, H226; ⚠ Aquatic Acute 1, H400; ⚠ Skin Irrit. 2, H315; ⚠ Eye Irrit. 2, H319; ⚠ Skin Sens. 1, H317; ⚠ STOT SE 3, H335	<0.5%

#### · Additional information:

For the wording of the listed hazard phrases refer to section 16.  
Note P. Benzol content in Solvent naphtha < 0,1%, therefore R45 "May cause cancer" is not necessary.

## SECTION 4: First aid measures

### · 4.1 Description of first aid measures

#### · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

#### · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Generally the product does not irritate the skin.

(Contd. on page 3)

# Material Safety Data Sheet

according to Regulation (EC) 1907/2006, Article 31

Product name: **TPC 128**

Revision : 25.05.2018

Page : 3 / 8



Version Number: 6

(Contd. of page 2)

- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:**  
Mouth respiratory protective device.  
Wear self-contained respiratory protective device.

## SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 4)

# Material Safety Data Sheet

according to Regulation (EC) 1907/2006, Article 31

Product name: TPC 128

Revision : 25.05.2018

Page : 4 / 8

 Teca-Print

Version Number: 6

(Contd. of page 3)

## · 8.1 Control parameters

· <b>Ingredients with limit values that require monitoring at the workplace:</b>	
<b>108-65-6 2-methoxy-1-methylethyl acetate</b>	
WEL	Short-term value: 548 mg/m <sup>3</sup> , 100 ppm Long-term value: 274 mg/m <sup>3</sup> , 50 ppm Sk
<b>1333-86-4 Carbon black</b>	
WEL	Short-term value: 7 mg/m <sup>3</sup> Long-term value: 3.5 mg/m <sup>3</sup>
<b>1330-20-7 Xylene, mixed isomers</b>	
WEL	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk, BMGV
· <b>Ingredients with biological limit values:</b>	
<b>1330-20-7 Xylene, mixed isomers</b>	
BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

· **Additional information:** The lists valid during the making were used as basis.

## · 8.2 Exposure controls

### · **Personal protective equipment:**

#### · **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.

#### · **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### · **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### · **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Butyl rubber, BR

#### · **Eye protection:**



Tightly sealed goggles

GB

(Contd. on page 5)

# Material Safety Data Sheet

according to Regulation (EC) 1907/2006, Article 31

Product name: TPC 128

Revision : 25.05.2018

Page : 5 / 8



Version Number: 6

(Contd. of page 4)

<b>· 9.1 Information on basic physical and chemical properties</b>	
<b>· General Information</b>	
<b>· Appearance:</b>	
Form:	Pasty
Colour:	According to product specification
<b>· Odour:</b> Characteristic	
<b>· Change in condition</b>	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	> 150 °C
<b>· Flash point:</b> 44 °C (Abel Pensky)	
<b>· Ignition temperature:</b> 315 °C	
<b>· Auto-ignition temperature:</b> Product is not selfigniting.	
<b>· Explosive properties:</b> Product does not present an explosion hazard.	
<b>· Explosion limits:</b>	
Lower:	0.7 Vol %
Upper:	7.5 Vol %
<b>· Vapour pressure at 20 °C:</b> 5 hPa	
<b>· Density:</b> Not determined.	
<b>· Solubility in / Miscibility with water:</b> Not miscible or difficult to mix.	
<b>· Viscosity:</b>	
Dynamic:	Not determined.
VOC (EC)	32.48 %
<b>· 9.2 Other information</b> No further relevant information available.	

## SECTION 10: Stability and reactivity

**10.1 Reactivity** No further relevant information available.

**· 10.2 Chemical stability**

**· Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

**· 10.3 Possibility of hazardous reactions** No dangerous reactions known.

**· 10.4 Conditions to avoid** No further relevant information available.

**· 10.5 Incompatible materials:** No further relevant information available.

**· 10.6 Hazardous decomposition products:** No dangerous decomposition products known.

## SECTION 11: Toxicological information

**· 11.1 Information on toxicological effects**

**· Acute toxicity** Based on available data, the classification criteria are not met

**· LD/LC50 values relevant for classification:**

**64742-95-6 Solvent naphtha (petroleum), light arom.**

Oral	LD50	3,592 mg/kg (rat)
------	------	-------------------

Dermal	LD50	3,160 mg/kg (rab)
--------	------	-------------------

Inhalative	LC50/4 h	>10.2 mg/l (rat)
------------	----------	------------------

**· Primary irritant effect:**

**· Skin corrosion/irritation** Based on available data, the classification criteria are not met.

(Contd. on page 6)

# Material Safety Data Sheet

according to Regulation (EC) 1907/2006, Article 31

Product name: TPC 128

Revision : 25.05.2018

Page : 6 / 8



Version Number: 6

- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Harmful to aquatic organisms  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

## SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

### European waste catalogue

08 03 12*	waste ink containing hazardous substances
-----------	---

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

## SECTION 14: Transport information

- |                                       |  |
|---------------------------------------|--|
| · <b>14.1 UN-Number</b>               | UN1210   |
| · <b>ADR, IMDG, IATA</b>              |  |
| · <b>14.2 UN proper shipping name</b> | 1210 PRINTING INK, ENVIRONMENTALLY HAZARDOUS   |
| · <b>ADR</b>                          | PRINTING INK (Solvent naphtha (petroleum), light aromatic, Hydrocarbon, C10, aromatics, <1% naphthalene), MARINE POLLUTANT |
| · <b>IMDG</b>                         |  |

[(Contd. on page 7)]

# Material Safety Data Sheet

according to Regulation (EC) 1907/2006, Article 31




Product name: TPC 128

Revision : 25.05.2018

Page : 7 / 8

 Teca-Print

Version Number: 6

· IATA	PRINTING INK
· 14.3 Transport hazard class(es)	
· ADR, IMDG	
 	
· Class	3 Flammable liquids.
· Label	3
· IATA	
	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: isobutyl methacrylate
· Marine pollutant:	Yes Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler):	30
· EMS Number:	F-E,S-D
· Stowage Category	A
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1210 PRINTING INK, 3, III, ENVIRONMENTALLY HAZARDOUS

GB

(Contd. on page 8)

# Material Safety Data Sheet

according to Regulation (EC) 1907/2006, Article 31

Product name: **TPC 128**

Revision : 25.05.2018

Page : 8 / 8



Version Number: 6

## SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**  
E2 Hazardous to the Aquatic Environment  
P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 40
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**  
H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H400 Very toxic to aquatic life.  
H411 Toxic to aquatic life with long lasting effects.
- **Department issuing SDS:** Product safety department
- **Contact:** msds@teca-print.com
- **Abbreviations and acronyms:**  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
Flam. Liq. 3: Flammable liquids – Category 3  
Acute Tox. 4: Acute toxicity – Category 4  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
Skin Sens. 1: Skin sensitisation – Category 1  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
Asp. Tox. 1: Aspiration hazard – Category 1  
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2