

Material Safety Data Sheet

according to Regulation (EC) 1907/2006, Article 31

Product name : Härter HM

Revision : 25.08.2014

Version : 1

Print date : 25.08.2014



Page : 1 / 9

01 Identification of the substance/preparation and of the company/undertaking

1.1 Product identifier

Product name
Härter HM

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Additive

1.3 Details of the supplier of the safety data sheet

Manufacturer / Supplier:

TECA-PRINT AG
Bohlstrasse 17, Postfach
CH - 8240 Thayngen/Schweiz
Phone: +41 (0) 52 645 20 00
Fax: +41 (0) 52 645 21 01
E-mail: info@teca-print.com

1.4 Emergency information:

Schweizerisches Toxikologisches Infozentrum > 24 Stunden täglich : CH - nationaler Notruf für Vergiftungsnotfälle
= 145 oder Telefon : ++41 (0) 44 251 51 51

02 Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02



GHS08

Signal word

Danger

Hazard-determining components of labelling:

Aromatisches Polyisocyanat
m-tolylidene diisocyanate

Material Safety Data Sheet

according to Regulation (EC) 1907/2006, Article 31

Product name : Härter HM

Revision : 25.08.2014 Version : 1

Print date : 25.08.2014



Page : 2 / 9

Hazard statements

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.

Precautionary statements

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P280	Wear protective gloves / eye protection.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable

vPvB: Not applicable

03 Composition/information on ingredients

3.2 Chemical characterization: Substances

Description

Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 53317-61-6	Aromatisches Polyisocyanat ⚠ Eye Irrit. 2, H319; Skin Sens. 1, H317	50-100%
CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226	10-25%
CAS: 1330-20-7 EINECS: 215-535-7	xylene ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	10-25%
CAS: 100-41-4 EINECS: 202-849-4	ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 4, H332	2.5-10%
CAS: 26471-62-5 EINECS: 247-722-4	m-tolylidene diisocyanate ⚠ Acute Tox. 2, H330; ⚠ Resp. Sens. 1, H334; Carc. 2, H351; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	< 1%

04 First aid measures

4.1 Description of first aid measures:

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air and to be sure call for a doctor.

Material Safety Data Sheet

according to Regulation (EC) 1907/2006, Article 31

Product name : Härter HM

Revision : 25.08.2014 Version : 1

Print date : 25.08.2014



Page : 3 / 9

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

05 Firefighting measures

5.1 Extinguishing media:

Suitable extinguishing agents:

CO₂, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable extinguishing agents:

Water with full jet

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters:

Protective equipment:

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

06 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

07 Handling and storage

7.1 Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Material Safety Data Sheet

according to Regulation (EC) 1907/2006, Article 31

Product name : Härter HM

Revision : 25.08.2014 Version : 1

Print date : 25.08.2014



Page : 4 / 9

Storage:

Requirements to be met by storerooms and receptacles:

No special requirements.

Information about storage in one common storage facility:

Not required.

Further information about storage conditions:

Keep container tightly sealed.

7.3 Specific end use(s):

No further relevant information available.

08 Exposure controls/personal protection

Additional information about design of technical facilities:

No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:	
108-65-6 2-methoxy-1-methylethyl acetate	
WEL	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
1330-20-7 xylene	
WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
100-41-4 ethylbenzene	
WEL	Short-term value: 552 mg/m ³ , 125 ppm Long-term value: 441 mg/m ³ , 100 ppm Sk
26471-62-5 m-tolyldiene diisocyanate	
WEL	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO

Ingredients with biological limit values:

1330-20-7 xylene	
BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

Additional information:

The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygiene measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.

Material Safety Data Sheet

according to Regulation (EC) 1907/2006, Article 31

Product name : Härter HM

Revision : 25.08.2014

Version : 1

Print date : 25.08.2014



Page : 5 / 9

Avoid contact with the eyes.
Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

09 Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information	
Appearance	
Form:	Liquid
Colour:	Yellowish
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point /Melting range:	Undetermined.
Boiling point /Boiling range:	> 145 °C
Flash point:	41 °C (Abel Penski)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature :	315 °C
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limit :	
Lower:	1,1 Vol %
Upper:	10,8 Vol %
Vapour pressure at 20 °C:	6,7 hPa
Density at 20 °C:	1,15 g/cm ³
Relative density:	Not determined.
Vapour density:	Not determined.

Material Safety Data Sheet

according to Regulation (EC) 1907/2006, Article 31

Product name : Härter HM



Revision : 25.08.2014 Version : 1

Print date : 25.08.2014

Page : 6 / 9

Evaporation rate:	Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water):	Not determined.
Viscosity:	
Dynamic at 20 °C:	Not determined.
Kinematic:	Not determined.
VOC (EC):	33,00 %

9.2 Other information

No further relevant information available.

10 Stability and reactivity

10.1 Reactivity

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions:

No dangerous reactions known.

10.4 Conditions to avoid:

No further relevant information available.

10.5 Incompatible materials:

No further relevant information available.

10.6 Hazardous decomposition products:

No dangerous decomposition products known.

11 Toxicological information

11.1 Information on toxicological effects

Acute toxicity:

LD/LC50 values relevant for classification:

1330-20-7 xylene

Oral	LD50	;	4300 mg/kg (rat)
Dermal	LD50	;	2000 mg/kg (rabbit)

Primary irritant effect::

on the skin: No irritant effect.

on the eye: Irritating effect.

Sensitization: Sensitization possible through inhalation.
Sensitization possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful
Irritant

12 Ecological information

12.1 Toxicity:

Aquatic toxicity:

No further relevant information available.

Material Safety Data Sheet

according to Regulation (EC) 1907/2006, Article 31

Product name : Härter HM



Revision : 25.08.2014 Version : 1

Print date : 25.08.2014

Page : 7 / 9

12.2 Persistence and degradability:

No further relevant information available.

12.3 Bioaccumulative potential:

No further relevant information available.

12.4 Mobility in soil:

No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects

No further relevant information available.

13 Disposal considerations

13.1 Waste treatment methods

Recommendation:

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue:


08 03 12:	waste ink containing dangerous substances
-----------	---

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations.

14 Transport information

14.1	UN-Number ADR, IMDG, IATA	UN1210
14.2	UN proper shipping name ADR IMDG, IATA	1210 PRINTING INK RELATED MATERIAL PRINTING INK RELATED MATERIAL
14.3	Transport hazard class(es) ADR, IMDG, IATA	 Class: 3 Flammable liquids. Label: 3
14.4	Packing group: ADR, IMDG, IATA	III
14.5	Environmental hazards: Marine pollutant:	No
14.6	Special precautions for user Danger code (Kemler): EMS Number:	Warning: Flammable liquids. 30 F-E,S-D

Material Safety Data Sheet

according to Regulation (EC) 1907/2006, Article 31

Product name : Härter HM

Revision : 25.08.2014

Version : 1

Print date : 25.08.2014



Page : 8 / 9

14.7	Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:		
ADR		
Limited quantities (LQ)	5L	
Excepted quantities (EQ)	Code: E1	
	Maximum net quantity per inner packaging: 30 ml	
	Maximum net quantity per outer packaging: 1000 ml	
Transport category	3	
Tunnel restriction code	D/E	
IMDG		
Limited quantities (LQ)	5L	
Excepted quantities (EQ)	Code: E1	
	Maximum net quantity per inner packaging: 30 ml	
	Maximum net quantity per outer packaging: 1000 ml	
UN "Model Regulation":		UN1210, PRINTING INK RELATED MATERIAL, 3, III

15 Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H412	Harmful to aquatic life with long lasting effects.

Department issuing data sheet:

TECA-PRINT AG, Bohlstrasse 17, CH - 8240 Thayngen, Switzerland
msds@teca-print.com

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent

Material Safety Data Sheet

according to Regulation (EC) 1907/2006, Article 31

Product name : Härter HM



Revision : 25.08.2014 Version : 1

Print date : 25.08.2014

Page : 9 / 9

LD50: Lethal dose, 50 percent
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Flam. Liq. 3: Flammable liquids, Hazard Category 3
Acute Tox. 4: Acute toxicity, Hazard Category 4
Acute Tox. 2: Acute toxicity, Hazard Category 2
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Carc. 2: Carcinogenicity, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3